

[USPTO PATENT FULL-TEXT AND IMAGE DATABASE](#)[Home](#)[Quick](#)[Advanced](#)[Pat Num](#)[Help](#)[Bottom](#)[View Cart](#)[Add to Cart](#)[Images](#)

( 1 of 1 )

**United States Patent  
Siddall****8,786,454  
July 22, 2014**

Air flow sensor

**Abstract**

A device for identifying the air flow condition within a clothes dryer having a lint filter, an exhaust passage, and a blower is disclosed. The device includes a sensor, an input having a first end connected to the sensor and a free second end, wherein the free second end is adapted to be disposed within the clothes dryer, upstream from a filter, and wherein the sensor detects a differential between an operating pressure at the free second end of input versus a reference pressure to thereby determine whether a sufficient vacuum is present within the clothes dryer, and an output that provides an output characteristic based on the differential, wherein the output characteristic changes from a first characteristic to a second characteristic when the differential surpasses a differential threshold.

**Inventors:** Siddall; John (Leland, MI)**Applicant:** Name City State Country Type

Siddall; John Leland MI US

**Assignee:** World Magnetics Company (Traverse City, MI)**Family ID:** 41695837**Appl. No.:** 12/543,799**Filed:** August 19, 2009**Prior Publication Data**Document Identifier

US 20100045472 A1

Publication Date

Feb 25, 2010

**Related U.S. Patent Documents**Application Number

61189935

Filing Date

Aug 25, 2008

Patent NumberIssue Date**Current U.S. Class:****340/626;** 34/88; 34/558; 73/700**Current CPC Class:**

D06F 58/22 (20130101); D06F 2105/58 (20200201); D06F 2103/28 (20200201); D06F 2105/60 (20200201); D06F

2103/00 (20200201); D06F 2103/36 (20200201); D06F  
2103/30 (20200201); D06F 58/50 (20200201)**Current International Class:**

G08B 21/00 (20060101)

**Field of Search:**

;340/603,626 ;73/700 ;34/88,89,558

---

**References Cited [Referenced By]**

---

**U.S. Patent Documents**

<a href="#">2577104</a>	December 1951	Butler
<a href="#">2941308</a>	June 1960	Cobb et al.
<a href="#">3286508</a>	November 1966	Spiegel
<a href="#">3639998</a>	February 1972	Mason
<a href="#">3718982</a>	March 1973	Deaton
<a href="#">3999440</a>	December 1976	Kain
<a href="#">4700492</a>	October 1987	Werner et al.
<a href="#">5097606</a>	March 1992	Harmelink et al.
<a href="#">6220092</a>	April 2001	Catbagan
<a href="#">6328647</a>	December 2001	Traudt
<a href="#">6587767</a>	July 2003	Letang et al.
<a href="#">6637127</a>	October 2003	Reede et al.
<a href="#">6655047</a>	December 2003	Miller, II
<a href="#">6785981</a>	September 2004	Harpenau
<a href="#">7237298</a>	July 2007	Reindle et al.
<a href="#">8061058</a>	November 2011	Harpenau

*Primary Examiner:* Bugg; George*Assistant Examiner:* Labbees; Edny*Attorney, Agent or Firm:* Honigman Miller Schwartz and Cohn LLP

---

**Parent Case Text**

---

**RELATED APPLICATION**

This application claims priority under 35 U.S.C. .sctn.119(e) to the U.S. Provisional Patent Application No. 61/189,935 filed on Aug. 25, 2008, the contents of which are fully incorporated herein by reference.

---

**Claims**

---

What is claimed is:

1. A device for identifying an air flow condition within a plurality of clothes dryers, each having: a door, a lint filter and a blower, the device comprising: a housing containing a power supply; a sensor disposed within the housing; a tubular member having a first end connected to the sensor and a second end that extends beyond an outer surface of the housing, wherein the tubular member defines a passageway extending between the first end and the second end such that the first end is in fluid communication with atmosphere that surrounds the outer surface of the housing, wherein the tubular member is retractably connected to housing and sensor such that a majority portion of tubular member is contained within housing when the device is not being used and can be extended therefrom beyond the outer surface of the housing and into a working position, wherein the tubular member is a flexible plastic tube and is extendable through the door

when arranged in a closed orientation without materially affecting the operation of the clothes dryer, wherein the second end of the tubular member is adapted to be disposed within the clothes dryer, upstream from a filter, and wherein the sensor detects a differential between an operating pressure at the free second end of the tubular member versus a reference pressure to thereby determine whether a sufficient vacuum is present within the clothes dryer; and an output that provides an output characteristic when the differential is less than a pre-determined differential threshold, wherein the output characteristic changes from a first characteristic to a second characteristic when the differential surpasses the pre-determined differential threshold, wherein the device is a handheld, portable device that can readily identify the flow condition in a plurality of clothes dryers.

2. The portable test device according to claim 1, further comprising: a housing, wherein the sensor is disposed within the housing, and wherein the tubular member is a tubular member and the second end of the tubular member extends outside of the housing.

3. The portable test device according to claim 2, wherein the tubular member is retractable such that second end of tubular member extends between a first operating position and a second non-operating position.

4. The portable test device according to claim 1, wherein the sensor includes a device selected from the group consisting of a transducer and a normally open pressure vacuum differential switch.

5. The portable test device according to claim 1, wherein the sensor includes two or more pressure vacuum differential switches to identify more than one vacuum conditions within the clothes dryer.

6. The portable test device according to claim 1, wherein the output includes one or more light emitting diodes.

7. The portable test device according to claim 6, wherein the output further includes an alarm that activates when the output characteristic is the second characteristic.

8. The portable test device according to claim 7, wherein the alarm is selected from the group consisting of a smoke alarm, a fire alarm, a carbon monoxide detector and any combination thereof.

9. The portable test device according to claim 7, wherein the alarm is communicatively attached to a receiver of a third party service provider.

10. The portable test device according to claim 1, wherein the reference pressure is the environmental pressure outside of the clothes dryer.

11. A method comprising the steps of: providing a portable test device having an air flow sensor, a tubular member having a first end connected to the air flow sensor and a second end that extends beyond an outer surface of the housing, wherein the tubular member defines a passageway extending between the first end and the second end such that the first end is in fluid communication with atmosphere that surrounds the outer surface of the housing, wherein the tubular member is retractably connected to housing and sensor such that a majority portion of tubular member is contained within housing when the portable test device is not being used and can be extended therefrom beyond the outer surface of the housing and into a working position, wherein the tubular member is a flexible plastic tube; interfacing the portable test device with a working device having an exhaust passage, wherein the working device is a clothes dryer having: a door, a lint filter and a blower, wherein the interfacing step includes inserting the second end of the tubular member into a clothes drying area of the clothes dryer, upstream from the lint trap, the exhaust passage and the blower; closing the door of the clothes dryer such that the second end remains within the clothes drying area; activating the clothes dryer for arrangement in an on condition; comparing internal pressure within the clothes dryer against an environmental pressure outside of the clothes dryer to identify whether a sufficient vacuum is present within the clothes dryer; determining an output characteristic when the difference between the internal pressure and the environmental pressure is less than a pre-determined threshold; and providing the output characteristic, wherein the detection occurs without modification of the dryer, wherein the tubular member is adapted to extend through the door when arranged in a closed orientation without materially affecting the operation of the clothes dryer.

12. The method according to claim 11, wherein the output characteristic identifies an abnormal condition when the difference between the pressure outside of the clothes dryer and the pressure in the clothes drying area is at or substantially around a pre-defined threshold difference.
13. The method according to claim 12, wherein the output includes an alarm, and further comprising the steps of: activating the alarm when the output characteristic identifies an abnormal condition.
14. The method according to claim 13, wherein the step of activating an alarm further comprises the sub-step of: sounding an audible alarm.
15. The method according to claim 13, wherein the step of activating an alarm further comprises the sub-step of: sending a communication that signifies the output characteristic.
16. The method according to claim 15, wherein the communication is sent to a third party service provider.
17. The method according to claim 15, wherein the communication is sent to a consumer communication device.
18. The method of detecting an airflow condition in a clothes dryer according to claim 11, wherein the portable test device includes one or more light emitting diodes and wherein the output characteristic of a normal condition and the output characteristic of an abnormal condition are differentiated by an activation of the one or more light emitting diodes.

---

### *Description*

---

## BACKGROUND

A device for identifying the air flow condition within a clothes dryer having a lint filter, an exhaust passage, and a blower is disclosed. The device includes a sensor, an input having a first end connected to the sensor and a free second end, wherein the free second end is adapted to be disposed within the clothes dryer, upstream from a filter, and wherein the sensor detects a differential between an operating pressure at the free second end of input versus a reference pressure to thereby determine whether a sufficient vacuum is present within the clothes dryer, and an output that provides an output characteristic based on the differential, wherein the output characteristic changes from a first characteristic to a second characteristic when the differential surpasses a differential threshold.

## SUMMARY

A device for identifying the air flow condition within a clothes dryer is disclosed. The device comprises a sensor, an input having a first end connected to the sensor and a free second end, wherein the free second end is adapted to be disposed within a clothes dryer, upstream from a filter, and wherein the pressure sensor detects a differential between an operating pressure at the free second end of input versus a second pressure, and an output that provides an output characteristic based on the differential, wherein the output characteristic changes from a first characteristic to a second characteristic when the differential surpasses a differential threshold.

Upon further study of the specification and appended claims, further features and advantages of this invention will become apparent to those skilled in the art.

## BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure will now be described, by way of example, with reference to the accompanying drawings, in which:

FIG. 1 is a diagrammatic representation of an air flow detection unit in accordance with an exemplary embodiment of the invention.



In an embodiment, output 20 may include one or more light sources to indicate the condition of switch 28 and the associated circuit to which output 20 is connected. In an embodiment, output 20 includes two light emitting diodes ("LEDs"). In an embodiment, a first one of two LEDs emits a first light when the pressure condition within passage 26 is maintained below the threshold pressure and a second of two LEDs emits a second light when the pressure condition within passage 26 exceeds the threshold differential. After considering this disclosure, it will be readily apparent to one of ordinary skill in the art that any combination of LED's may be used to signal the condition of the pressure within passage 26. For example, one LED may emit light upon a first pressure condition and both LEDs may emit light based on a second condition. Alternatively, one LED may be employed such that it only emits light when the pressure switch detects a rise in pressure or vice versa.

In an embodiment, output 20 may alternatively, or additionally, be connected to, or include, an alarm 30 to signal the pressure condition within passage 26. In an embodiment, alarm 30 may exhibit an audible signal when the differential exceeds the threshold as discussed above. In an embodiment, alarm 30 may be a selected from the group consisting of a smoke alarm, a fire alarm a carbon monoxide detector or the like. In an embodiment, alarm 30 may be any type of device such as a cell phone, computer, email account or the like. In an embodiment, alarm 30 may be connected to a third party service provider such as a security company, a fire station, a police station or the like. In an embodiment, alarm 30 may be any combination of the foregoing.

Now that exemplary embodiments of unit 10 have been described in a manner as to apprise one of ordinary skill in the art how to make and carry out the unit, a method of operating the unit will be described. As described above, unit 10 can be used in connection with a clothes dryer. Unit 10 can be permanently installed in connection with a clothes dryer, or alternatively, unit 10 can be portable to facilitate testing on multiple units. In an embodiment and to facilitate operation, second end of tubular member of input 18 is inserted within the clothes dryer, upstream from the lint trap and the blower. Positioning second end of tubular member downstream of input 18 will decrease the efficacy of the results as the lint can provide, or supplement, the impendence of passage and the inventor hereof has realized higher accuracy by testing the passage upstream of the lint trap. In addition, due to the location of unit at an upstream position and because it is detecting the presence or absence of a vacuum, lint and other material do not enter the switch and will not impede input.

Accordingly, sensor 16 can thereby determine whether the pressure differential within the inside of the dryer is sufficient when the dryer is turned on. Depending on the condition of sensor 16, an output is provided to alert whether the differential between the pressure within the dryer and the environmental pressure is sufficient. As set forth above, the output may be provided via LEDs, an audible alarm, a signal to a third party service provider or any combination of the foregoing.

The present invention has been particularly shown and described with reference to the foregoing embodiments, which are merely illustrative of the best modes for carrying out the invention. It should be understood by those skilled in the art that various alternatives to the embodiments of the invention described herein may be employed in practicing the invention without departing from the spirit and scope of the invention as defined in the following claims. It is intended that the following claims define the scope of the invention and that the method and apparatus within the scope of these claims and their equivalents be covered thereby. This description of the invention should be understood to include all novel and non-obvious combinations of elements described herein, and claims may be presented in this or a later application to any novel and non-obvious combination of these elements. Moreover, the foregoing embodiments are illustrative, and no single feature or element is essential to all possible combinations that may be claimed in this or a later application.

\* \* \* \* \*



- [Home](#)
- [Quick](#)
- [Advanced](#)
- [Pat Num](#)
- [Help](#)